

Revision Date: 07/29/2021

- i. Insert type roof drains reducing the piping area are permitted on re-roofing projects if the diameter of the roof leader is 4 inches or greater to provide adequate drainage capacity and avoid overflowed leaks AND when drainage calculations confirm the existing leader piping diam rainfall.
- j. Reinforcing (-m) 4 (11 (hat) 4) (107 (e) 33 (-) T) 8 ((02 v T) 7 (e) 3) (34 r) (n) (4) (6) 24 (m) 4) 3 (e) 3 (s) (6) T) j.
- l. Roof 00vTj dge-notificator] 3 te 00 systems shall be a 01 project (n) go 4 go 2 (e) 4 (m) 6 (s) (a) -4 (i)
 - m. R Anchor arrays shall be provided new building roof-repl 3 t. 0acement projects be dis
 - i. Portable. 3 t. 0 anchor systems systems.
 - n. Provide grease resistt-rotective laye
 - o. Provide chemical 3 t. 0 resistt m T] 3 or fs ar T] 3 e present Re view exhate-c membrne. 3] T] 0 FM Global, 3 t. 0

2. Submittals to be review

- a. All proosed merials nd i 3 t. 0nstallion methods i 3 t. 0nform T] 3 ation
- b. All exposeolor selections-Design Profession T] 3 al
- c. FM Global requi 0vTj redescr is
- d. MS pr or to start of construction

